

PANEL

Screen Size	55"
Resolution	1,920 x 1,080 (FHD)
Brightness(Typ.,cd/m ²)	500

CONNECTIVITY

Input	HDMI (2), DP, DVI-D, Audio In, OPS, USB 3.0
Output	DP, External Speaker Out
External Control	RS232C in/out, RJ45, IR / Light Sensor, Pixel Sensor

PHYSICAL SPECIFICATION

Bezel Width	7.4 mm (T/L/R/B even)
Monitor Dimension (W x H x D)	1,230 x 714 x 32 mm
Weight (Head)	20.7 kg
VESA™ Standard Mount Interface	400 x 400

ENVIRONMENT CONDITIONS

Operation Temperature	0°C to 40°C
Operation Humidity	10 % to 80 %

POWER

Power Supply	100-240 V~, 50/60 Hz
--------------	----------------------

Power Type	Built-In Power
-------------------	----------------

POWER CONSUMPTION

Typ.	120W
-------------	------

Smart Energy Saving	85W
----------------------------	-----

STANDARD(CERTIFICATION)

Safety	UL / cUL / CB / TUV / KC
---------------	--------------------------

EMC	FCC Class "A" / CE / KCC
------------	--------------------------

ErP / Energy Star	Yes (EU Only) / Yes (Energy Star 7.0)
--------------------------	---------------------------------------

MEDIA PLAYER COMPATIBILITY

OPS type compatible	Yes
----------------------------	-----

External Media player Attachable	Yes (MP500/MP700)
---	-------------------

SOFTWARE COMPATIBILITY

Content Management Software	SuperSign Premium
------------------------------------	-------------------

Control and Monitoring Software	SuperSign C
--	-------------

ACCESSORY

Basic	Remote Controller (2ea batteries included), Power Cord, IR / Light Sensor Receiver, QSG, Regular Book (depend on regional standard), HDMI Cable
--------------	---

Optional	External Speaker (SP-2100), Stand(ST-200T), Wall Mount(LSW440S), Wi-Fi USB Dongle (AN-WF500), OPS Kits (KT-OPSA), Pixel Sensor (KT-SP0)
-----------------	---
